



mondial



## Sous-Chef

Tavoli refrigerati e congelatori  
Refrigerated and freezers tables



GAS  
R290

08c



TEMPERATURE RANGE

-22° +8° C

IDEAL FOR



**CARATTERISTICHE TECNICHE** - Technical features

	<b>SOUS-CHEF 2 PX</b>	<b>SOUS-CHEF 2 NX</b>	<b>SOUS-CHEF 3 PX</b>	<b>SOUS-CHEF 3 NX</b>	<b>SOUS-CHEF 4 PX</b>	<b>SOUS-CHEF 4 NX</b>
Temperatura - <i>Temperature</i>	-2°C +8°C	-18°C -22°C	-2°C +8°C	-18°C -22°C	-2°C +8°C	-18°C -22°C
Gas refrigerante - <i>Refrigerant gas</i>	R290	R290	R290	R290	R290	R290
Classe climatica - <i>Climate Class</i>	4 (30°C-55%UR)	4 (30°C-55%UR)	4 (30°C-55%UR)	4 (30°C-55%UR)	4 (30°C-55%UR)	4 (30°C-55%UR)
Dimensioni (l x p x h) <i>Sizes (w x d x h)</i>	1350 x 700 x 950 mm		1800 x 700 x 950 mm		2250 x 700 x 950 mm	
Peso netto - <i>Net weight</i>	102	102	126	126	153	153
Peso lordo - <i>Gross weight</i>	127	142	158	180	196	210
Volume Lordo - <i>Gross volume</i>	260 l	260 l	400 l	400 l	570 l	570 l
Potenza - <i>Power</i>	350 W	700 W	350 W	820 W	330 W	920 W
Consumo - <i>Consumption</i>	2,5 kWh/24h	6,1 kWh/24h	2,9 kWh/24h	7,3 kWh/24h	3,8 kWh/24h	7,7 kWh/24h
Dimensioni imballo (l x p x h) <i>Packaging sizes (w x d x h)</i>	1390 x 740 x 970 mm		1840 x 740 x 970 mm		2290 x 740 x 970 mm	
Dati per il trasporto - <i>Transport data</i> (20 ft - 40 ft - 40 hc - 13,60 mt)	24/50/50/53		18/38/38/40		16/32/32/34	
Ripiani - <i>Shelves</i>	4 rimovibili/removable		6 rimovibili/removable		8 rimovibili/removable	
Classe energetica - <i>Energy efficiency class</i>						

✓ **Griglie rimovibili GN1/1:  
4 (N°2 per ogni porta)**  
Adjustable shelves GN1/1:  
4 (N.2 for each door)

✓ **Rispetto ambientale: Gas R290**  
Environmentally friendly: R290

✓ **Alzatina compressa (100 mm)**  
On dotation splash back (100 mm)



SOUS-CHEF 2



SOUS-CHEF 3



SOUS-CHEF 4

**APPROFONDIMENTO** - More details

**GASTRONORM 1/1 GN**

**Mobile in lamiera d'acciaio inox AISI 304**  
AISI 304 stainless steel sheet cabinet

**Vasca in lamiera d'acciaio inox AISI 304**  
AISI 304 stainless steel sheet tank

**Testato a 38°C**  
Tested at 38°C

**Raffreddamento ventilato**  
Ventilated cooling

